

**1.- Identification code of the product type and any other element allowing identification of the product:**

Dry-pressed ceramic tiles with water absorption  $AA \leq 0.5\%$  for internal and external walls and floors with antislip properties.

**2.- Intended use:**

Internal and external walls and floors with antislip properties

**3.- Name or registered mark and address of the manufacturer:**

Alaplana cerámica  
Nueva Alaplana SL  
C/Pinet, 1 P.I. Els Plans 12592 Chilches (Castellon) ESPAÑA

**4.- System of assessment and verification of constancy of performance (AVCP)**

System 4

**5.- Name and identification number of notified laboratory, if relevant:**

Not relevant

**6.- Declared Performances:**

SERIE 5		
Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	Clase A1-A1 <sub>fl</sub>	EN 14411:2012
Release of dangerous substance for: - Cadmium - Lead	PND PND	
Breaking Strength	> 1300 N	
Slipperiness PTV (wet), slider 57, CEN/TS 16165:2016	> 35	
Tactility	PND	
Adhesion strength Cementitious adhesive type C2	> 1 N/mm <sup>2</sup>	
Thermal shock resistance	Pass	
Durability for: - Internal use - External use	Pass Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Nules, a 1/07/2017

Javier Aparici Bartoll  
Apoderado

**alaplana.**  
CERÁMICA  
NUEVA ALAPLANA, SL  
CIF: B-12930491  
C/ El Pinet, 1 P.I. "Els Plans"  
12592 CHILCHES (Castellón)