

MODEL: UP
SIZE: 25 x 70
PRODUCT TYPE: RED BODY TILES
GROUP: B III

DATE: 07/04/2017

TESTS CARRIED OUT	RESULTS	
UNE-EN ISO 10545-2 DIMENSIONS AND SURFACE QUALITY		CONFORMS TO STANDARD
UNE-EN ISO 10545-3 WATER ABSORPTION	AVERAGE VALUE (%)	16 %
UNE-EN-ISO 10545-4 MODULUS OF RUPTURE	BREAKING STRENGTH (N)	600 - 900 N
	MODULUS OF RUPTURE (N / mm ²)	20 - 30 N/mm²
UNE-EN ISO 10545-7 RESISTANCE TO SURFACE ABRASION	CLASS ABRASION (PEI)	NOT APPLY
UNE-EN ISO 10545-9 RESISTANCE TO THERMAL SHOCK	THERMAL SHOCK	RESISTS
UNE-EN ISO 10545-11 CRAZING RESISTANCE	RESULTS	RESISTS
UNE-EN ISO 10545-13 CHEMICAL RESISTANCE	AMMONIUM CHLORIDE 100 g/l	GA
	SODIUM HYPOCHLORITE 20 mg/l	GA
	HYDROCHLORIC ACID 3 %	CONFORMS TO STANDARD
	CITRIC ACID 100 g/l	
	POTASSIUM HYDROXIDE 30 g/l	
UNE-EN ISO 10545-14 STAIN RESISTANCE	GREEN AGENT IN LIGHT OIL	5
	IODINE SOLUTION IN ALCOHOL	5
	OLIVE OIL	5

OBSERVATIONS:

LABORATORY :



AZULEJOS FOSET, SLU, Camino del Palmeral, 10
12200 ONDA (Castellón) ESPAÑA